

STC828E - Rev 2- 31.01.05

CERTIFICATION CATEGORY II



KRYTECH 828-829

CE-Type Examination Certificates KRYTECH 828 : 0075/014/162/07/99/0065

KRYTECH 829 : 0075/014/162/07/99/0065 - Ext. N°01/11/00

issued by the approved body nr. 0075

I.F.T.H.. – Av. Guy de Collongue - F-69134 ECULLY CEDEX

These gloves conform to the provisions of Directive 89/686/EEC for protection against mechanical risks.



DESCRIPTION AND GENERAL PROPERTIES

White **seamless** gloves made of **Spectra®* / glass fibre / polyester.**

Elastic knitted wrist (natural rubber elastic bands).

Knit gauge: 10

Reference	Sizes available	Cuff end colour	Glove length (cm) typical values
Krytech 828	7	red	23
	8	blue	24
	9	green	26
	10	orange	27.5
	7	red	30
Krytech 829	8	blue	31
	9	green	32
	10	orange	33

Standard packaging:

- 1 glove per bag including information
 - 10 gloves per carton

"CE"-TYPE EXAMINATION RESULTS



PROTECTION AGAINST MECHANICAL RISKS

Levels of performance according to EN 388 standard

2	5	4	X
I	-	-	1
	-	1	→ puncture resistance (0 to 4)
I	I	└ → †	tear resistance (0 to 4)
I	\hookrightarrow	blad	de cut resistance (0 to 5)
ᆫ	• ab	rasi	on resistance (0 to 4)

X: Not applicable

It is not recommended to use these gloves next to moving machinery. These gloves are not designed to protect against puncture, electrical and thermal risks nor for use in contact with chemicals.



^{*} Registered trademark of Honeywell

KRYTECH 828-829

SPECIFIC ADVANTAGES

- Seamless construction for higher comfort.
- Excellent hand fit and superior dexterity thanks to flexibility and elasticity.
- Very high cut resistance.
- Excellent abrasion resistance.
- Ambidextrous design : practical and economical.
- Extended cuff to protect forearm.
- Washable : increased service life.
- For food handling.
- White colour and fibres adapted to strict hygiene requirements applicable in food industries.

MAIN FIELDS OF USE

- Food handling e.g meat cutting
- Automotive and aeronautical industries
- Metal works

- Cutting plastic parts
- Printing works
- Paper industry

INSTRUCTIONS FOR USE

For enhanced safety and service life of the products:

- Store the gloves in their original packaging protected from light and humidity.
- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use in the workplace may differ from the "CE"- type tests.
- When liquid protection is required, these gloves can be used as an under-glove for cut resistance
- Put the gloves on dry, clean hands.
- Cleaning instructions according to the label:

70°C

Λ

A

laundering at 70°C maximum, bleaching authorized (5.25% Sodium hypochlorite solution - standard bleach - diluted in 1-10 parts water), dry cleaning and tumble drying permitted.

- Caution: using the gloves inadequately or submitting them to another cleaning or laundering process can alter their performance levels.
- Inspect the gloves for cracks or snags before reusing them.

