



# **KROFLEX 840**

## **DESCRIPTIONS and GENERAL PROPERTIES**

Glove with synthetic textile cut-resistant support with palm and fingers coated with latex crinkle blue

**Curved fingers** and **contoured** palm

Elastic knitted wrist (natural rubber elastic wrist band)

**Non-slip finish** on the palm and fingers

	<b>Sizes available</b>	<b>Glove length (cm)</b> Nominal values
<b>KROFLEX 840</b>	7	23
	8	23.5
	9	25
	10	26

Standard packaging:

- 1 **pair** per bag with information leaflet
- **12** pairs per polybag
- **72** pairs per carton

## **"CE"-TYPE EXAMINATION RESULTS**

These gloves do not protect against chemical risks



**Protection against mechanical risks**

Levels of performance according to EN 388 standards.

2 5 4 2  
| | | |  
| | | | ↪ puncture resistance (0 to 4)  
| | | | ↪ tear resistance (0 to 4)  
| | | | ↪ blade cut resistance (0 to 5)  
| | | | ↪ abrasion resistance (0 to 4)



**Protection against heat**

Levels of performance according to EN 407 standards.

x 2 x x x x  
| | | |  
| | | | ↪ radiating heat (0 to 4)  
| | | | ↪ convective heat (0 to 4)  
| | | | ↪ contact heat (0 to 4)

# **KROFLEX 840**

## **SPECIFIC ADVANTAGES**

- Excellent comfort and flexibility thanks to the interior textile (seamless)
- Optimal cut resistance, level 5.
- Good grip for picking up parts safely thanks to anti-slip embossing
- Good thermal insulation of the hand
- Comfort and flexibility

## **MAIN FIELDS OF USE**

- Glass industries
  - Handling glass sheets
- Ceramics and plastics industries, composite material industries
  - Post-injection handling hot plastic parts
  - Handling composite materials after baking
- Environment
  - Waste collect and treatment

## **INSTRUCTION FOR USE AND STORAGE**

### **For enhanced safety and service life of the gloves:**

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- Store the glove in their original packaging protected from heat, light and humidity.
- Put the gloves on dry, clean hands.
- Ensure the inside of the gloves is dry before putting them on again.
- Caution: improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.
- Inspect the gloves for cracks or snags before reusing them.
- It is not recommended for persons sensitized to dithiocarbamates or thiazoles to use these gloves, nor to use them next to moving machinery.
- For more information about performances and uses, contact your distributor or the Technical Customer Service MAPA PROFESSIONNEL ([stc.mapaspontex@ms.hutchinson.fr](mailto:stc.mapaspontex@ms.hutchinson.fr))

**"CE" DECLARATION OF CONFORMITY**

The Company

**MAPA s.n.c.**

57, rue de Villiers  
BP 190  
92205 Neuilly-sur-Seine Cedex - France

declares that the following MAPA PROFESSIONNEL protective glove :

**KROFLEX 840**

conforms to the glove which is the subject of "CE" certificate of conformity

**nr 0075/014/162/08/11/0473**

issued by the notified body nr **0075**

**C.T.C**

4 rue H FRENKEL - F-69367 LYON CEDEX 07

It conforms to the provisions of directive **89/686/CEE**, designed for protection against **mechanical risks and contact heat**,

and is manufactured in conformance with the following **European Standards** :  
**EN 420, EN 388 and EN 407.**

Prepared at Beauvais, on January 13th, 2009

**MAPA S.N.C.**  
57, rue de Villiers  
BP 190  
92205 NEUILLY-SUR-SEINE Cedex  
N. OGER  
Technical Services Pole